Revision Date 03/13/2020

### 1 Identification

- · Product identifier
- · Product Name: STM4055W
- · Relevant identified uses of the substance or mixture. Sealant
- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- · Manufactured for: Seal Corp USA, Inc. 1175 E. Diamond Ave. Evansville, IN 47711 812-868-0790
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Sol. 1 H228 Flammable solid.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS07

GHS0

· Signal word Danger

(Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet acc. to OSHA HCS

Revision Date 03/13/2020

Product Name: STM4055W

· Hazard statements

Flammable solid.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.* 

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.


Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



 $\frac{2}{1}$  Health = 2

3 Fire = 3

PHYSICAL HAZARD  $\boxed{0}$  Physical Hazard = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazardous components:		
64742-49-0	Naphtha (petroleum), hydrotreated light, low boil	25-50%
13463-67-7	titanium dioxide	2.5-10%
1305-78-8	calcium oxide	≤ 1%

(Contd. on page 3)

Revision Date 03/13/2020

Product Name: STM4055W

(Contd. of page 2)

#### · Additional information:

It is highly unlikely the powders and pigments compounded within this product would pose a hazardous risk from inhalation as they are no longer a respirable particulate. Exposure to these ingredients as used in sealants, putties, bedding compounds and other non-sprayable products is highly unlikely. The concentrations listed in the composition section are percent by weight unless a gas. Gas concentrations are expressed in percent by volume.

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Call a doctor immediately.

Overexposure, remove to fresh air and seek medical attention.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Dried solids can burn and release toxic fumes and vapors.

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose of contaminated material as waste in accordance with federal state and local regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

Protective Action Criteria for Chemicals	
· PAC-1:	
13463-67-7 titanium dioxide	30 mg/m3
112945-52-5 Amorphous Silica	18 mg/m3
1305-78-8 calcium oxide	6 mg/m3
57-11-4 stearic acid, pure	14 mg/m3
1	(Contd. on page 4

USA

Revision Date 03/13/2020

Product Name: STM4055W

	(Contd. of page 3
· PAC-2:	
13463-67-7 titanium dioxide	330 mg/m3
112945-52-5 Amorphous Silica	100 mg/m3
1305-78-8 calcium oxide	110 mg/m3
57-11-4 stearic acid, pure	150 mg/m3
PAC-3:	•
13463-67-7 titanium dioxide	2,000 mg/m3
112945-52-5 Amorphous Silica	630 mg/m3
1305-78-8 calcium oxide	660 mg/m3
57-11-4 stearic acid, pure	910 mg/m3

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

- · Information about protection against explosions and fires: Keep container closed when not in use.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1346	13463-67-7 titanium dioxide	
PEL	Long-term value: 15* mg/m³	
	*total dust	
REL	See Pocket Guide App. A	
TLV	Long-term value: 10 mg/m³	
	withdrawn from NIC	
1305	-78-8 calcium oxide	
PEL	Long-term value: 5 mg/m³	
REL	Long-term value: 2 mg/m³	
TLV	Long-term value: 2 mg/m³	

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Revision Date 03/13/2020

Product Name: STM4055W

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses with side shields.
- · Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Pasty Solid
Color:	White
Odor:	Petroleum-like
Odor threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point:	Undetermined.
Boiling point:	104 °C (219.2 °F)
Flash point:	18 °C (64.4 °F)
Flammability (solid, gaseous):	Not determined.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self igniting.
Danger of explosion:	Product is not explosive. However, formation of flammable air/vapor mixtures are possible.
Flammable limits:	
Lower:	0.9%
Upper:	6.7%

US

(Contd. on page 6)

Revision Date 03/13/2020

Product Name: STM4055W

(Contd. of page 5) · Vapor pressure: Not applicable. · Specific gravity at 20 °C (68 °F): 1.04 g/cm³ (8.6788 lbs/gal) · Relative density Not determined. · Vapor density Not applicable. · Evaporation rate < 1.0 · Solubility in / Miscibility with Soluble. Water: · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not applicable. Kinematic: > 20.5 cStOther information  $VOC\ content = <449\ g/l$ 

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flames, sparks, hot surfaces, ignition sources.
- · Incompatible materials: Reacts with oxidizing agents.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: May irritate the skin.
- · on the eye: May irritate the eye.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
13463-67-7 titanium dioxide	2B
14808-60-7 non-respirable quartz	1
NTP (National Toxicology Program)	
14808-60-7 non-respirable quartz	K
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: Not expected to be harmful to aquatic organisms

(Contd. on page 7)

Revision Date 03/13/2020

Product Name: STM4055W

(Contd. of page 6)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

At present there are no ecotoxicological assessments.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Small amounts can be disposed of with household waste after the product has cured or skinned over. Larger quantities should be disposed of according to state and local regulation.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1325

· UN proper shipping name

• **DOT** Flammable solids, organic, n.o.s. (Naphtha) • **IMDG, IATA** FLAMMABLE SOLID, ORGANIC, N.O.S. (Naphtha)

- · Transport hazard class(es)
- DOT



\* Class 4.1 Flammable solids, self-reactive substances and solid desensitized explosives

- **Label** 4.1

(Contd. on page 8)

Revision Date 03/13/2020

Product Name: STM4055W

(Contd. of page 7)

#### · IMDG, IATA



· Class 4.1 Flammable solids, self-reactive substances and solid

desensitized explosives

· Label 4.1

· Packing group

· **DOT, IMDG, IATA** 

• Environmental hazards: Not applicable.

• Special precautions for user Warning: Flammable solids, self-reactive substances and solid

desensitized explosives

• EMS Number: F-A,S-G

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": UN1325 FLAMMABLE SOLID, ORGANIC, N.O.S. (NAPHTHA), 4.1, II

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

Please contact The Ruscoe Company for more information regarding Proposition 65 on this product.

· (DSL) Canada Domestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· New Jersey	Right-to-Know List:
--------------	---------------------

1317-65-3 Limestone

13463-67-7 titanium dioxide

1305-78-8 calcium oxide

· New Jersey Special Hazardous Substance List:

1305-78-8 calcium oxide

CO, R1

Pennsylvania Right-to-Know List:

1317-65-3 Limestone

13463-67-7 titanium dioxide

(Contd. on page 9)

Revision Date 03/13/2020

Product Name: STM4055W

	(Contd. of page 8)
1305-78-8 calcium oxide	
· Pennsylvania Special Hazardous Substance List:	
None of the ingredients is listed.	
· Cancerogenity categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
13463-67-7 titanium dioxide	A4
14808-60-7 non-respirable quartz	A2
MAK (German Maximum Workplace Concentration)	·
13463-67-7 titanium dioxide	<i>3A</i>
14808-60-7 non-respirable quartz	1
· NIOSH-Ca (National Institute for Occupational Safety and Health)	·
13463-67-7 titanium dioxide	
14808-60-7 non-respirable quartz	

- · National regulations:
- Information about limitation of use: Use by properly trained workers recommended.
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, The Ruscoe Company makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will The Ruscoe Company or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Date of preparation / last revision 02/25/2020
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Sol. 1: Flammable solids - Category 1

(Contd. on page 10)

*Revision Date 03/13/2020* 

Product Name: STM4055W

(Contd. of page 9)

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3